



## Operating manual For low pressure relief valve Type LPS... ZM-B... and ZM-B/R...

**LPS25**



**LPSK25**



**ZM-B15  
ZM-B25  
ZM-B/R**



### Contents

1	General information .....	2
2	Warranty provisions .....	2
3	Purpose .....	2
3.1	Intended use .....	2
3.2	Assembly work on the pressure regulator .....	2
4	Safety provisions .....	3
5	Material resistance .....	3
6	Startup .....	3
6.1	Before installation .....	3
6.2	Installation .....	3
6.3	Assembly position and installation .....	3
6.4	Configuring the setpoint .....	5
7	Impulse line (C-connection) .....	5
8	Maintenance and repairs .....	5
8.1	Inspection intervals .....	5
9	Model selection .....	6
10	Code: ZM-B15, relief valve .....	7
11	Code: ZM-B25, relief valve .....	8
12	Code: ZM-B/R15, non return valve .....	9
13	Code: ZM-B/R25, non return valve .....	10
14	Code: LPSK25, relief valve .....	11
15	Code: LPS25, relief valve .....	12

## 1 General information

This operating manual is for handling pressure regulators. Operating errors can be prevented only with knowledge of this operating manual.

Operating personnel must be informed about the contents of this operating manual.

Improper use may result in hazard to life for the user or other third parties and/or damage to other material assets.

We reserve the right to make technical modifications for improvement purposes to the comparisons and information in this operating manual.

## 2 Warranty provisions

There shall be no liability, or the warranty shall be void under the following conditions:

- The information and instructions of the operating manual are not followed.
- The devices are improperly used.
- The devices are used for purposes other than their intended one.
- Any type of functional changes were conducted without the written permission of ZIMMERLI MESSTECHNIK AG.
- Disregard of the applicable safety regulations when operating the device.
- Guards were not used or functionality was disabled.

Only approved, original spare parts must be used when replacing parts and/or for procuring spare parts.

## 3 Purpose

These type of pressure regulators are suitable for various tasks (e.g. inerting containers with inactive gases). The degree of protection for the standard design is IP40 and IP54 with weather protection.

The exact design is customized and must therefore be taken from the device's technical information.

### 3.1 Intended use

Ambient temperature:	-20 °C up to +40 °C
Ambient pressure:	0.8 to 1.1 bar
Medium pressure:	Permissible PN, maximum p <sub>1</sub> , maximum p <sub>2</sub> according to the data sheet
Medium temperature:	According to sealing material, see data sheet
Degree of protection:	IP40, with IP54 weather protection, ZM-B/R IP68

Limitations of the medium: No combustible gases in an explosive concentration. Exception, ATEX-certified devices according to:

- II 2 G Ex h IIB T6 Gb
- II 3 G Ex h IIC T6 Gc
- II 2 D Ex h IIIC T6 Db
- II 3 D Ex h IIIC T6 Dc

External radiation (electromagnetic, ionizing radiation, ultrasound): none (if such radiation is present in the area used, the hazard must be taken into account and assessed by the user.) Keep the devices free of dust (dust thickness smaller than 1 mm).

### 3.2 Assembly work on the pressure regulator

The user and operator must take measures for mounting, disassembly, and maintenance work of and on the pressure regulator in areas with explosive atmospheres to prevent these operations from creating sources of ignition.

## 4 Safety provisions

Any work on or with the device may be performed only by qualified personnel who are familiar with the applicable regulations on operating pressure regulators and/or pressure containers.

If disassembling safety equipment is required for installation, it must be assembled and inspected immediately once the work has concluded.

Do not exceed the operating pressure. It is specified on the nameplate of each device.

When using the device, the provisions regarding the filling material must be followed.

Natural regulations regarding usage and test intervals must be followed.

## 5 Material resistance

Since the operator chose the material, the supplier cannot provide any guarantees regarding material resistance. It is the operator's responsibility to ensure that the material of the devices, including seals and add-on components (e.g., pressure gauges, pilot regulator, etc.) are adequately resistant against the medium.

## 6 Startup

### 6.1 Before installation

Before installation, perform a visual inspection on the device to determine any transport damage. The device's performance data must be reviewed (max. inlet pressure, secondary pressure, etc.).

The values noted on the nameplate are the values measured in our functional test.

The resistance of the materials has to be checked (see the corresponding chapter of this operating manual).

Newly installed pipelines must be fully rinsed clean to eliminate mechanical residues. It must be ensured that the pressure regulator is connected at the local equipotential bonding, either through an adequate and permanent connection to metallic pipes or via a direct connection to local equipotential bonding.

### 6.2 Installation

Always install the low pressure regulator as close as possible to the process tank or consumer within non-turbulent flow.

Be mindful of the flow direction! (Marked on the housing with an arrow). Otherwise, there is the risk of damaging the pressure regulator.

### 6.3 Assembly position and installation

Take note of the diaphragm installation position! (Horizontal diaphragm or vertical diaphragm). Sealed devices are set to the desired pressure according to the ordered position. If the devices are configured by the user, then this also must take place in the subsequent installation position.

The preferred mounting position and/or position of the diaphragm is as follows according to device type:

- ZM-B15, 25: Horizontal diaphragm housing (vertical: alternatively permissible).  
Assembly with the spring dome facing down is permissible only upon consultation.
- ZM-B/R: Horizontal diaphragm housing, spring dome on top
- LPS25: Vertical diaphragm housing (horizontal: alternatively permissible).  
Assembly with the spring dome facing down is permissible only upon consultation.


Horizontal		Mounting position (diaphragm)		Vertical	
	Recommended mounting position		Recommended mounting position (ZM-B only with option /E, depending on the medium)		
	Spring dome on bottom side, only on request / dry gases		Only dry gases		

**Important:** The setpoint depends on the diaphragm position and must be adjusted according to the assembly position.

The configuration can be sealed using the lateral hole in the setting screw. Factory-sealed devices are set to the specified pressure.

Assembly must be performed on  $p_1$ , primary side, without turbulent flow. To that end a straight inlet piping of  $5 \times DN$  is recommended.

Furthermore, it is recommended that you install one shut-off valve each before and after the pressure regulator to simplify any maintenance work. Furthermore, a suitable filter must be installed before the pressure regulator in case of dirty gases or if there is a hazard of solid particles.



Avoid pressure shocks after assembly and always open shut-off valves slowly!

## 6.4 Configuring the setpoint

**Always open the valves in lines before or after the pressure regulator slowly and avoid pressure shocks!**

### **Spring-loaded model ZM-B und LPS:**

Slowly open the valve or ball valve before or after the pressure regulator and set it to a small flow of approx. 1 to 2 Nm<sup>3</sup>/h.

Set the desired pressure by turning the setting screw (6 mm hexagon socket).

Warning! Observe the maximum values on the nameplate.

Clockwise rotation = Decreasing primary pressure  $p_1$

Counterclockwise rotation = Increasing primary pressure  $p_1$

### **Dome-loaded model ZM-B and LPS with option /De /Ds:**

With an additional pilot controller, the dome pressure can be set to the desired value. Up to 1000 mbar and/or 2000 mbar of dome pressure is permissible depending on the device type. Precise adjustments can also be made via the setting screw on the spring dome.

### **Reflux blocking valve ZM-B/R:**

By turning the setting screw (6 mm hexagon socket), the differential pressure can be adjusted.

Warning! Observe the maximum values on the nameplate.

Clockwise rotation = Decreasing primary pressure  $p_1$

Counterclockwise rotation = Increasing primary pressure  $p_1$

## 7 Impulse line (C-connection)

An impulse line must be able to communicate with the  $p_1$  side of the valve under any circumstances. Accordingly, no valves or other flow resistances may be present in the primary, non turbulent flow area between the device and impulse line pickup. Otherwise, the device is not functional and may even be destroyed.

## 8 Maintenance and repairs

The previously mentioned pressure regulators work without auxiliary energy and are maintenance-free. Additional queries may be processed only by specifying the serial number.

The serial number must be specified for spare part orders.

Device returns for repair or modification can be accepted only if they have been cleaned and have a completed RMA according to the applicable regulations. In the case of hazardous media, we recommend returning the device disassembled and cleaned.

### 8.1 Inspection intervals


An annual review of the function or maintenance is recommended depending on the characteristics of the medium and the respective operating states. Depending on these results, the testing/maintenance interval can be shortened or extended by the operator/user.

## 9 Model selection

### Geräteauslegung

### Model selection

### Sélection de l'appareil



### Anwendungsdaten

Zur optimalen Auslegung eines Überström- oder Druckhalteventil ZM-B15 sind mindestens folgende Angaben wichtig:

#### Behälter Befüllungsgradient

Befüllungsgradient bzw. Pumpenleistung wie folgt:

$$Q = \quad \text{Nm}^3/\text{h}$$

$$V = \quad \text{Nm}^3$$

#### Inertgas

Sekundär- oder Gegendruck  $p_2$  ist üblicherweise der atmosphärische Druck.

$$p_1 = \quad \text{mbar g primär}$$

$$p_2 = \quad \text{mbar g sekundär}$$

#### Werkstoff

Welcher Werkstoff ist ausreichend chemisch beständig?

- Edelstahl
- Hastelloy C
- Kunststoff (auf Anfrage)

#### Betriebsart

- Standard / Überdruck
- Negativdruck / Unterdruck
- Domgesteuert

#### Montage\*

- Direkt auf Tank, vertikal
- Direkt an Tank, horizontal
- Innerhalb von Gebäuden
- Im Freien mit Schutzhaube
- In Abluftleitung mit C-Anschluss\* und separater Impulsleitung vom Prozess

### Application data

For correct model selection of ZM-B15 back pressure relief valve, the following specifications are essential:

#### Tank filling rate

Tank filling rate or Pump capacity as follows:

$$Q = \quad \text{Nm}^3/\text{h}$$

$$V = \quad \text{Nm}^3$$

#### Inert gas

Secondary pressure or counter pressure  $p_2$  is normally atmospheric pressure.

$$p_1 = \quad \text{mbar g primary}$$

$$p_2 = \quad \text{mbar g secondary}$$

#### Material of construction

What material of construction is durable enough?

- SST
- Hastelloy C
- plastic (on request)

#### Mode

- Gauge Pressure Blanketing, Standard
- Negative pressure service
- Dome loaded service

#### Installation\*

- Top mounted on tank, vertical
- Side mounted at tank, horizontal
- In door
- Out door with weather protection
- In exhaust pipe with C-Connection\* and pulse line from process

### Données de l'application

Les renseignements suivants représentent un minimum nécessaire pour effectuer le dimensionnement optimal d'un ZM-B15.

#### Gradient de remplissage du réservoir

Gradient de remplissage, resp. rendement de la pompe comme suit:

$$Q = \quad \text{Nm}^3/\text{h}$$

$$V = \quad \text{Nm}^3$$

#### Gaz inerte

La pression secondaire ou contre-pression  $p_2$  est normalement atmosphérique.

$$p_1 = \quad \text{mbar g primaire}$$

$$p_2 = \quad \text{mbar g secondaire}$$

#### Matériaux de construction

Quel matériaux est suffisamment chimico-résistant ?

- Acier inoxydable
- Hastelloy C
- Matière plastique (nous consulter)

#### Mode de fonctionnement

- Pression relative, Standard
- Conditions en dépression
- Piloté par le dôme

#### Montage\*

- Direct sur cuve, en vertical
- Direct sur cuve, en horizontal
- Locaux dans un bâtiment
- En extérieur avec protection
- Conduite avec raccord-C\* et prise d'impulsion au niveau du procédé

# 10 Code: ZM-B15, relief valve

<b>ZM-B</b>	P40 / IP54 (Option /Ws)	<b>Funktion</b>	Überdruck	Gauge Pressure	Pression relative	520 mbar
<b>ZM-B/D</b>	P68	Function	Domgesteuert	Dome loaded	Dôme	2000 mbar (2500 mbar)
<b>ZM-B/Ds</b>	P40	Fonction	Fremd/Pilot	Remote /Pilot	Pilotage/ indirect	2000 mbar (2500 mbar)
<b>ZM-B/N</b>	P40 / IP54 (Option /Ws)		Negativdruck	Negative pressure	Pression negative	-220 mbar
<b>ZM-B/NDs</b>	P40		Fremd/Pilot	Remote/Pilot	Pilotage/indirect	-1000 mbar
	<b>15</b> DN15, PN40, B1	<b>Grösse</b>	Einbaulänge	Lay length	Encombrement	150 mm / ~6.7 kg
	<b>15</b> DN15, PN40, D	Size	Einbaulänge	Lay length	Encombrement	150 mm / ~6.7 kg
	<b>15</b> ½", 150 lbs	Dimension	Einbaulänge	Lay length	Encombrement	180 mm / ~6.4 kg
	<b>15</b> ½", 300 lbs		Einbaulänge	Lay length	Encombrement	189 mm / ~7.7 kg
	<b>15</b> G½ (½" BSP)		Einbaulänge	Lay length	Encombrement	152 mm / ~5.5 kg
	<b>15</b> ½" NPT-F		Einbaulänge	Lay length	Encombrement	152 mm / ~5.5 kg
	<b>15</b> TriClamp		Einbaulänge	Lay length	Encombrement	141 mm / ~5.6 kg
	<b>S</b>	<b>Material</b>	Edelstahl	SST	INOX	1.4404
	<b>H</b>	Material	Hastelloy C	Hastelloy C	Hastelloy C	C276
	<b>X</b>	Matériaux	Sonder auf Anfrage	Special on request	Nous consulter	(PP, PVDF) <sup>1)</sup>
	<b>-FD</b>	DN15, PN40	Flansch	Flange	Brides	DIN / EN 1092-1, B1
	<b>-FDN</b>	DN15, PN40	Flansch / Nut	Flange / Groove	Brides / à gorge	DIN / EN 1092-1, D
	<b>-FA1</b>	½", 150 lbs	Flansch	Flange	Brides	ANSI
	<b>-FA3</b>	½", 300 lbs	Flansch	Flange	Brides	ANSI
	<b>-GD1</b>	G½ (½" BSP)	Gewinde	Thread	Fileté	DIN / EN
	<b>-GN1</b>	½" NPT-F	Gewinde	Thread	Fileté	ANSI
	<b>-TCB</b>	TriClamp	TriClamp	Ø 50.5 mm	DIN32676, B	DIN / EN
	<b>-XX</b>		Sonder auf Anfrage	Special on request	Spécial nous consulter	
Öffnungsdruck [mbar] Opening pressure Pression de ouvre ≤ 4 ~ 3...9 ~ 5...15 ~ 8...32 ~ 10...80 ≤ 2 ~ 3...9 ~ 5...15 ~ 8...32	<b>-P</b>	<b>Membrane</b>	PTFE	-20/+180 °C	Ø 200 mm	
	<b>-V</b>	Diaphragm	Viton®	-20/+130 °C	Ø 200 mm	
	<b>10</b>	<b>Federbereich</b>	<b>Horizontal</b> <sup>2)</sup>	<b>Vertical</b> <sup>3)</sup>	<b>Typ, Type, Type</b>	<b>Dom, Dome, Dôme</b>
	<b>20</b>	p <sub>1</sub> , primär	6 – 10 mbar	3 – 8 mbar	ZM-B, ZM-B/D/Ds	(max 2013 mbar)
	<b>50</b>	Spring range	10 – 20 mbar	5 – 20 mbar	ZM-B, ZM-B/D/Ds	(max 2055 mbar)
	<b>100</b>		13 – 50 mbar	8 – 50 mbar	ZM-B, ZM-B/D/Ds	(max 2100 mbar)
	<b>200</b>		15 – 100 mbar	10 – 100 mbar	ZM-B, ZM-B/D/Ds	(max 2200 mbar)
	<b>500</b>	p <sub>1</sub> , primary	20 – 200 mbar	15 – 200 mbar	ZM-B, ZM-B/D/Ds	(max 2500 mbar)
	<b>0</b>	Plage de réglage	N/A*	-5 – 0 mbar	ZM-B/N, ZM-B/NDs	(min -1000 mbar)
	<b>10</b>		p <sub>1</sub> , primaire	-10 – -2 mbar	-15 – -3 mbar	ZM-B/N, ZM-B/NDs
<b>50</b>	-55 – -5 mbar		-60 – -10 mbar	ZM-B/N, ZM-B/NDs	(min -1000 mbar)	
<b>100</b>	-115 – -15 mbar		-120 – -20 mbar	ZM-B/N, ZM-B/NDs	(min -1000 mbar)	
<b>200</b>	-215 – -45 mbar	-220 – -50 mbar	ZM-B/N, ZM-B/NDs	(min -1000 mbar)		
	<b>180</b>	<b>Sitz</b>	Kv = 6.5 / 18 mm			
		<b>Siege</b>				
		<b>Optionen,</b>	<b>Options, Options</b>			
		<b>/C</b>	C (Impulsleitung)	C (pulse line)	C (ligne d'impulsion)	G¼ (¼" BSP)
		<b>/E</b>	E (Drainage)	E (Drain)	E (Vidage)	G¼ (¼" BSP)
		<b>/S1</b> <sup>4)</sup>	Manometerstutzen	Gauge nozzle	Raccord manomètre	G¼ (¼" BSP, p <sub>1</sub> )
		<b>/S2</b> <sup>4)</sup>	Manometerstutzen	Gauge nozzle	Raccord manomètre	G¼ (¼" BSP, p <sub>2</sub> )
		<b>/Sp</b>	Eingestellt/plombiert	Adjusted and sealed	Ajusté et plombé	
		<b>/Ws</b>	Wetterschutz	Weather protection	Avec protection	IP54 PP / Polypropylen
		<b>/C2.2</b>	EN 10204-2.2	EN 10204-2.2	EN 10204-2.2	II 2 G Ex h IIB T6 Gb II 3 G Ex h IIC T6 Gc II 2 D Ex h IIIC T6 Db II 3 D Ex h IIIC T6 Dc
		<b>/C3.1</b>	EN 10204-3.1	EN 10204-3.1	EN 10204-3.1	
		<b>/Cp</b>	Einstellprotokoll	Test protocol	Protocole de réglage	
		<b>/Ex</b>	ATEX Zulassung	ATEX approval	Certificat ATEX	
		<b>/Ff</b>	Öl- Fettfrei	Certificate degreasing	Sans Huile ni Graisse	
		<b>/FDA</b>	FDA-Bescheinigung	FDA approval	Certificat FDA	
		<b>/LT</b>	Lecktest	Leakage test	Essai de fuite	
		<b>/XPZ</b>	Poliert mit Zertifikat	Polished w/certified	Poli, avec Certificat	
<b>Beispiel, Example, Exemple</b>						
<b>ZM-B</b>	<b>15</b>	<b>S</b>	<b>-FD</b>	<b>-P</b>	<b>100</b>	<b>180 /Sp/C3.1/Cp/Ex</b>

## Hinweise,

**N/A\*** nicht anwendbar  
<sup>1)</sup> Siehe Typ: **LPSK...**  
<sup>2)</sup> Für Flüssigkeiten & Gase  
<sup>3)</sup> Nur für Gasanwendungen  
<sup>4)</sup> Manometer optional verfügbar

**Hints,**  
 not applicable  
 See Type: **LPSK...**  
 For liquids and gas  
 Gas applications only  
 Pressure gauge optionally available

**Remarque**  
 non applicable  
 S.V.P. remarque aussi Type: **LPSK...**  
 Pour liquides et gaz  
 Pour les applications de gaz  
 Manomètre disponible en option

# 11 Code: ZM-B25, relief valve

<b>ZM-B</b>	IP40 / IP54 (Option /Ws)	<b>Funktion</b>	Überdruck	Gauge Pressure	Pression relative	520 mbar	
<b>ZM-B/D</b>	IP68	Function	Domgesteuert	Dome loaded	Dôme	2000 mbar (2500 mbar)	
<b>ZM-B/Ds</b>	IP40	Fonction	Fremd/Pilot	Remote/Pilot	Pilotage/indirect	2000 mbar (2500 mbar)	
<b>ZM-B/N</b>	IP40 / IP54 (Option /Ws)		Negativdruck	Negative pressure	Pression negative	-220 mbar	
<b>ZM-B/NDs</b>	IP40		Fremd/Pilot	Remote/Pilot	Pilotage/indirect	-1000 mbar	
	<b>25</b> DN25, PN40, B1	<b>Größe</b>	Einbaulänge	Lay length	Encombrement	160 mm / ~7.7 kg	
	<b>25</b> DN25, PN40, D	Size	Einbaulänge	Lay length	Encombrement	160 mm / ~7.7 kg	
	<b>25</b> 1", 150 lbs	Dimension	Einbaulänge	Lay length	Encombrement	195 mm / ~7.3 kg	
	<b>25</b> 1", 300 lbs		Einbaulänge	Lay length	Encombrement	208 mm / ~8.2 kg	
	<b>25</b> G¾ (¾" BSP)		Einbaulänge	Lay length	Encombrement	156 mm / ~5.7 kg	
	<b>25</b> G1 (1" BSP)		Einbaulänge	Lay length	Encombrement	170 mm / ~5.9 kg	
	<b>25</b> G1.5 (1½" BSP)		Einbaulänge	Lay length	Encombrement	156 mm / ~5.7 kg	
	<b>25</b> ¾" NPT-F		Einbaulänge	Lay length	Encombrement	156 mm / ~5.7 kg	
	<b>25</b> 1" NPT-F		Einbaulänge	Lay length	Encombrement	170 mm / ~5.7 kg	
	<b>25</b> 1.5" NPT-F		Einbaulänge	Lay length	Encombrement	180 mm / ~5.9 kg	
	<b>25</b> TriClamp		Einbaulänge	Lay length	Encombrement	141 mm / ~5.9 kg	
	<b>S</b>	<b>Material</b>	Edelstahl	SST	INOX	1.4404	
	<b>H</b>	Material	Hastelloy C	Hastelloy C	Hastelloy C	C276	
	<b>X</b>	Matériaux	Sonder auf Anfrage	Special on request	Spécial nous consulter	(PP, PVDF) <sup>1)</sup>	
	<b>-FD</b>	DN25, PN40	<b>Anschluss/Typ</b>	Flansch	Flange	Brides	
	<b>-FDN</b>	DN25, PN40	Connection/Type	Flansch / Nut	Flange / Groove	Brides / à gorge	
	<b>-FA1</b>	1", 150 lbs	Raccord/Type	Flansch	Flange	Brides	
	<b>-FA3</b>	1", 300 lbs		Flansch	Flange	Brides	
	<b>-GD2</b>	G¾ (¾" BSP)		Gewinde	Thread	Fileté	
	<b>-GD3</b>	G1 (1" BSP)		Gewinde	Thread	Fileté	
	<b>-GD4</b>	G1.5 (1½" BSP)		Gewinde	Thread	Fileté	
	<b>-GN2</b>	¾" NPT-F		Gewinde	Thread	Fileté	
	<b>-GN3</b>	1" NPT-F		Gewinde	Thread	Fileté	
	<b>-GN4</b>	1.5" NPT-F		Gewinde	Thread	Fileté	
	<b>-TCB</b>	TriClamp		TriClamp	Ø 50.5 mm	DIN32676, B	
	<b>-XX</b>			Sonder auf Anfrage	Special on request	Spécial nous consulter	
	<b>-P</b>	<b>Membrane</b>	Diaphragm	PTFE	-20/+180 °C	Ø 200 mm	
	<b>-V</b>	Membrane		Viton®	-20/+130 °C	Ø 200 mm	
		<b>Federbereich</b>	<b>Horizontal</b> <sup>2)</sup>	<b>Vertical</b> <sup>3)</sup>	<b>Typ, Type, Type</b>	<b>Dom, Dome, Dôme</b>	
		<b>10</b>	p <sub>1</sub> , primär	8 – 13 mbar	3 – 8 mbar	ZM-B, ZM-B/D/Ds	(max 2013 mbar)
		<b>20</b>		10 – 25 mbar	5 – 20 mbar	ZM-B, ZM-B/D/Ds	(max 2025 mbar)
		<b>50</b>		13 – 55 mbar	8 – 50 mbar	ZM-B, ZM-B/D/Ds	(max 2055 mbar)
		<b>100</b>	Spring range	15 – 100 mbar	10 – 100 mbar	ZM-B, ZM-B/D/Ds	(max 2100 mbar)
		<b>200</b>	p <sub>1</sub> , primary	20 – 200 mbar	15 – 200 mbar	ZM-B, ZM-B/D/Ds	(max 2200 mbar)
		<b>500</b>		25 – 500 mbar	20 – 500 mbar	ZM-B, ZM-B/D/Ds	(max 2500 mbar)
		<b>0</b>		N/A*	-5 – 0 mbar	ZM-B/N, ZM-B/NDs	(min -1000 mbar)
		<b>10</b>	Plage de réglage	-10 – -2 mbar	-15 – -3 mbar	ZM-B/N, ZM-B/NDs	(min -1000 mbar)
		<b>50</b>	p <sub>1</sub> , primaire	-55 – -5 mbar	-60 – -10 mbar	ZM-B/N, ZM-B/NDs	(min -1000 mbar)
		<b>100</b>		-115 – -15 mbar	-120 – -20 mbar	ZM-B/N, ZM-B/NDs	(min -1000 mbar)
		<b>200</b>		-215 – -45 mbar	-220 – -50 mbar	ZM-B/N, ZM-B/NDs	(min -1000 mbar)
		<b>180</b>	<b>Sitz</b>				
			Seat	Kv = 6.5 / 18 mm			
			Siège				
			<b>Optionen, Options, Options</b>				
			<b>/C</b>	C (Impulsleitung)	C (pulse line)	C (ligne d'impulsion)	G¾ (¾" BSP)
			<b>/E</b>	E (Drainage)	E (Drain)	E (Vidage)	G¾ (¾" BSP)
			<b>/S1</b> <sup>4)</sup>	Manometerstutzen	Gauge nozzle	Raccord manomètre	G¾ (¾" BSP, p <sub>1</sub> )
			<b>/S2</b> <sup>4)</sup>	Manometerstutzen	Gauge nozzle	Raccord manomètre	G¾ (¾" BSP, p <sub>2</sub> )
			<b>/Sp</b>	Eingestellt/plombiert	Adjusted and sealed	Ajusté et plombé	
			<b>/Ws</b>	Wetterschutz	Weather protection	Avec protection	IP54 PP/Polypropylen
			<b>/C2.2</b>	EN 10204-2.2	EN 10204-2.2	EN 10204-2.2	I 2 G Ex h IIB T6 Gb II 3 G Ex h IIC T6 Gc II 2 D Ex h IIIC T6 Db UI 3 D Ex h IIIC T6 Dc
			<b>/C3.1</b>	EN 10204-3.1	EN 10204-3.1	EN 10204-3.1	
			<b>/Cp</b>	Einstellprotokoll	Test protocol	Protocole de réglage	
			<b>/Ex</b>	ATEX Zulassung	ATEX approval	Certificat ATEX	
			<b>/FDA</b>	FDA-Bescheinigung	FDA approval	Certificat FDA	
			<b>/Ff</b>	Öl- Fettfrei	Certificate degreasing	Sans Huile ni Graisse	
			<b>/LT</b>	Lecktest	Leakage test	Essai de fuite	
			<b>/XPZ</b>	Poliert mit Zertifikat	Polished w/certified	Poli, avec Certificat	
<b>Beispiel, Example, Exemple</b>							
<b>ZM-B</b>	<b>25</b>	<b>S</b>	<b>-FD</b>	<b>-P</b>	<b>100</b>	<b>180</b>	<b>/Sp/C3.1/Cp/Ex</b>

Öffnungsdruck [mbar]
Opening pressure
Pression de ouvre
≤ 4
≤ 8
~ 3...9
~ 5...15
~ 8...32
~ 10...80
≤ 2
≤ 4
~ 3...9
~ 5...15
~ 8...32

## Hinweise,

- N/A\*** nicht anwendbar  
<sup>1)</sup> Siehe Typ: **LPSK...**  
<sup>2)</sup> Für Flüssigkeiten & Gase  
<sup>3)</sup> Nur für Gasanwendungen  
<sup>4)</sup> Manometer optional verfügbar

## Hints,

- not applicable  
 See Type: **LPSK...**  
 For liquids and gas  
 Gas applications only  
 Pressure gauge optionally available

## Remarque

- non applicable  
 S.V.P. remarque aussi Type: **LPSK...**  
 Pour liquides et gaz  
 Pour les applications de gaz  
 Manomètre disponible en option

## 12 Code: ZM-B/R15, non return valve

ZM-B/R	IP68	Funktion Function Fonction	Rückfluss-Sperrventil Reflux blocking valve Soupape anti-reflux	Druckverlust: Pressure drop: Perte de pression:	siehe Federbereich see spring range voir plage de réglage	
15	DN15, PN40, B1	<b>Grösse</b> Size Dimension	Einbaulänge	Lay length	Encombrement	150 mm / ~6.9 kg
15	DN15, PN40, D		Einbaulänge	Lay length	Encombrement	150 mm / ~6.9 kg
15	½", 150 lbs		Einbaulänge	Lay length	Encombrement	180 mm / ~6.6 kg
15	½", 300 lbs		Einbaulänge	Lay length	Encombrement	189 mm / ~7.9 kg
15	G½ (½" BSP)		Einbaulänge	Lay length	Encombrement	152 mm / ~5.7 kg
15	½" NPT-F		Einbaulänge	Lay length	Encombrement	152 mm / ~5.7 kg
15	TriClamp		Einbaulänge	Lay length	Encombrement	141 mm / ~5.8 kg
S		<b>Material</b> Material Matériaux	Edelstahl	SST	INOX	1.4404
X			Sonder auf Anfrage	Special on request	Spécial nous consulter	
-FD	DN15, PN40	<b>Anschluss/Typ</b> Connection/Typ Raccord/Type	Flansch	Flange	Brides	DIN / EN 1092-1, B1
-FDN	DN15, PN40		Flansch / Nut	Flange / Groove	Brides / à gorge	DIN / EN 1092-1, D
-FA1	½", 150 lbs		Flansch	Flange	Brides	ANSI
-FA3	½", 300 lbs		Flansch	Flange	Brides	ANSI
-GD1	G½ (½" BSP)		Gewinde	Thread	Fileté	DIN / EN
-GN1	½" NPT-F		Gewinde	Thread	Fileté	ANSI
-TCB	TriClamp		TriClamp	Ø 50.5 mm	DIN32676, B	DIN / EN
-XX			Sonder auf Anfrage	Special on request	Spécial nous consulter	
-P		<b>Membrane</b> Diaphragm Membrane	PTFE	-20/+180 °C	Ø 200 mm	
-V			Viton®	-20/+130 °C	Ø 200 mm	
10		<b>Federbereich</b> p <sub>1</sub> , primär  Spring range p <sub>1</sub> , primary  Plage de réglage p <sub>1</sub> , primaire	<b>Horizontal</b> <sup>1)</sup>		<b>Vertical</b> <sup>1)</sup>	
20			8 – 13 mbar	3 – 8 mbar	<b>Typ, Type, Type</b>	
50			10 – 25 mbar	5 – 20 mbar	ZM-B/R25	
100			13 – 55 mbar	8 – 50 mbar	ZM-B/R25	
200			15 – 100 mbar	10 – 100 mbar	ZM-B/R25	
500			20 – 200 mbar	15 – 200 mbar	ZM-B/R25	
1000			25 – 500 mbar	20 – 500 mbar	ZM-B/R25	
		100 – 1050 mbar	96 – 1046 mbar	ZM-B/R25		
180		<b>Sitz</b> Seat Siège	Kv = 6.5 / 18 mm			
<b>Optionen, /Options, /Options</b>						
/S1 <sup>2)</sup>		Manometerstutzen	Gauge nozzle	Raccord manomètre	G¼ (¼" BSP, p <sub>1</sub> )	
/S2 <sup>2)</sup>		Manometerstutzen	Gauge nozzle	Raccord manomètre	G¼ (¼" BSP, p <sub>2</sub> )	
/Sp		Eingestellt/plombiert	Adjusted and sealed	Ajusté et plombé		
/C2.2		EN 10204-2.2	EN 10204-2.2	EN 10204-2.2	II 2 G Ex h IIB T6 Gb II 3 G Ex h IIC T6 Gc II 2 D Ex h IIIC T6 Db II 3 D Ex h IIIC T6 Dc	
/C3.1		EN 10204-3.1	EN 10204-3.1	EN 10204-3.1		
/Cp		Einstellprotokoll	Test protocol	Protocole de réglage		
/Ex		ATEX Zulassung	ATEX approval	Certificat ATEX		
/Ff		Öl- Fettfrei	Certificate degreasing	Sans Huile ni Graisse		
/FDA		FDA-Bescheinigung	FDA approval	Certificat FDA		
/LT		Lecktest	Leakage test	Essai de fuite		
/XPZ		Poliert mit Zertifikat	Polished w/certified	Poli, avec Certificat		
<b>Beispiel, Example, Exemple</b>						
ZM-B/R	15	S	-FD	-P	100	180 /Sp/C3.1/Cp/Ex

### Hinweise,

<sup>1)</sup>Nur für Gasanwendungen  
<sup>2)</sup>Manometer optional verfügbar

### Hints,

Gas applications only  
Pressure gauge optionally available

### Remarque

Pour les applications de gaz  
Manomètre disponible en option

## 13 Code: ZM-B/R25, non return valve

ZM-B/R	IP68	Funktion Function Fonction	Rückfluss-Sperrventil Reflux blocking valve Soupape anti-reflux	Druckverlust: Pressure drop: Perte de pression:	siehe Federbereich see spring range voir plage de réglage	
25	DN25, PN40, B1	<b>Grösse</b> Size Dimension	Einbaulänge	Lay length	Encombrement	160 mm / ~7.7 kg
25	DN25, PN40, D		Einbaulänge	Lay length	Encombrement	160 mm / ~7.7 kg
25	1", 150 lbs		Einbaulänge	Lay length	Encombrement	195 mm / ~7.3 kg
25	1", 300 lbs		Einbaulänge	Lay length	Encombrement	208 mm / ~8.2 kg
25	G¾ (¾" BSP)		Einbaulänge	Lay length	Encombrement	156 mm / ~5.7 kg
25	G1 (1" BSP)		Einbaulänge	Lay length	Encombrement	170 mm / ~5.9 kg
25	G1.5 (1½" BSP)		Einbaulänge	Lay length	Encombrement	156 mm / ~5.7 kg
25	¾" NPT-F		Einbaulänge	Lay length	Encombrement	156 mm / ~5.4 kg
25	1" NPT-F		Einbaulänge	Lay length	Encombrement	170 mm / ~5.7 kg
25	1.5" NPT-F		Einbaulänge	Lay length	Encombrement	180 mm / ~5.9 kg
25	TriClamp	Einbaulänge	Lay length	Encombrement	141 mm / ~5.9 kg	
<b>S</b>		<b>Material</b> Material Matériaux	Edelstahl	SST	INOX	1.4404
<b>X</b>			Sonder auf Anfrage	Special on request	Spécial nous consulter	
	<b>-FD</b>	DN25, PN40	Flansch	Flange	Brides	DIN / EN 1092-1, B1
	<b>-FDN</b>	DN25, PN40	Flansch / Nut	Flange / Groove	Brides / à gorge	DIN / EN 1092-1, D
	<b>-FA1</b>	1", 150 lbs	Flansch	Flange	Brides	ANSI
	<b>-FA3</b>	1", 300 lbs	Flansch	Flange	Brides	ANSI
	<b>-GD2</b>	G¾ (¾" BSP)	Gewinde	Thread	Fileté	DIN / EN
	<b>-GD3</b>	G1 (1" BSP)	Gewinde	Thread	Fileté	DIN / EN
	<b>-GD4</b>	G1.5 (1½" BSP)	Gewinde	Thread	Fileté	DIN / EN
	<b>-GN2</b>	¾" NPT-F	Gewinde	Thread	Fileté	ANSI
	<b>-GN3</b>	1" NPT-F	Gewinde	Thread	Fileté	ANSI
	<b>-GN4</b>	1.5" NPT-F	Gewinde	Thread	Fileté	ANSI
	<b>-TCB</b>	TriClamp	TriClamp	Ø 50.5 mm DIN32676, B	Fileté	DIN / EN
	<b>-XX</b>		Sonder auf Anfrage	Special on request	Spécial nous consulter	
	<b>-P</b>	<b>Membrane</b> Diaphragm Membrane	PTFE	-20/+180 °C	Ø 200 mm	
	<b>-V</b>		Viton®	-20/+130 °C	Ø 200 mm	
	<b>10</b>	<b>Federbereich</b> p <sub>1</sub> , primär	<b>Horizontal</b> <sup>1)</sup> 8 – 13 mbar	<b>Vertical</b> <sup>1)</sup> 3 – 8 mbar	<b>Typ, Type, Type</b> ZM-B/R25	<b>p<sub>1</sub></b> (max), <b>p<sub>2</sub></b> (max) max. 2013 mbar
	<b>20</b>	Spring range	10 – 25 mbar	5 – 20 mbar	ZM-B/R25	max. 2025 mbar
	<b>50</b>	p <sub>1</sub> , primary	13 – 55 mbar	8 – 50 mbar	ZM-B/R25	max. 2055 mbar
	<b>100</b>	Plage de réglage	15 – 100 mbar	10 – 100 mbar	ZM-B/R25	max. 2100 mbar
	<b>200</b>	p <sub>1</sub> , primaire	20 – 200 mbar	15 – 200 mbar	ZM-B/R25	max. 2200 mbar
	<b>500</b>		25 – 500 mbar	20 – 500 mbar	ZM-B/R25	max. 2500 mbar
	<b>1000</b>		100 – 1050 mbar	96 – 1046 mbar	ZM-B/R25	max. 2500 mbar
	<b>180</b>	<b>Sitz</b> Seat Siège	Kv = 6.5 / 18 mm			
		<b>Optionen, /Options, /Options</b>				
		<b>/S1</b> <sup>2)</sup>	Manometerstutzen	Gauge nozzle	Raccord manomètre	G¾ (¾" BSP, p <sub>1</sub> )
		<b>/S2</b> <sup>2)</sup>	Manometerstutzen	Gauge nozzle	Raccord manomètre	G¾ (¾" BSP, p <sub>2</sub> )
		<b>/Sp</b>	Eingestellt/plombiert	Adjusted and sealed	Ajusté et plombé	
		<b>/C2.2</b>	EN 10204-2.2	EN 10204-2.2	EN 10204-2.2	II 2 G Ex h IIB T6 Gb II 3 G Ex h IIC T6 Gc II 2 D Ex h IIIC T6 Db II 3 D Ex h IIIC T6 Dc
		<b>/C3.1</b>	EN 10204-3.1	EN 10204-3.1	EN 10204-3.1	
		<b>/Cp</b>	Einstellprotokoll	Test protocol	Protocole de réglage	
		<b>/Ex</b>	ATEX Zulassung	ATEX approval	Certificat ATEX	
		<b>/FDA</b>	FDA-Bescheinigung	FDA approval	Certificat FDA	
		<b>/Ff</b>	Öl- Fettfrei	Certificate degreasing	Sans Huile ni Graisse	
		<b>/LT</b>	Lecktest	Leakage test	Essai de fuite	
		<b>/XPZ</b>	Poliert mit Zertifikat	Polished w/certified	Poli, avec Certificat	
<b>Beispiel, Example, Exemple</b>						
ZM-B/R	25	S	-FD	-P	100	180 /Sp/C3.1/Cp/Ex

### Hinweise,

<sup>1)</sup>Nur für Gasanwendungen  
<sup>2)</sup>Manometer optional verfügbar

### Hints,

Gas applications only  
 Pressure gauge optionally available

### Remarque

Uniquement pour les applications gaz  
 Manomètre disponible en option

# 14 Code: LPSK25, relief valve

<b>LPSK</b> <b>LPSK/D</b> <b>LPSK/Ds</b> <b>LPSK/N</b> <b>LPSK/NDs</b>	IP40 / IP54 <sup>2)</sup> IP68 IP40 / IP68 IP40 / IP54 <sup>2)</sup> IP40	<b>Funktion</b> Function Fonction	Überdruck Domgesteuert Fremd/Pilot Negativdruck Neg. Fremd/Pilot	Gauge Pressure Dome loaded Remote/Pilot Negative pressure Neg. Integral/Pilot	Pression relative Piloté par le dôme Pilotage/indirect Pression negative Neg. Pilotage/indirect	500 mbar 1000 mbar (1500 mbar) <sup>2,3)</sup> 1000 mbar (1500 mbar) <sup>2,3)</sup> -120 mbar 1000 mbar <sup>4)</sup>
	<b>25</b> <b>25</b>	DN 25, PN16 1", 150 lbs	<b>Grösse</b> Size Dimension	Einbaulänge Sonder auf Anfrage	Lay length Special on request	Encombrement 140 x 100 mm Spécial nous consulter
	<b>PP</b> <b>PV</b>		<b>Material<sup>6)</sup></b> Material <sup>6)</sup> Matériaux <sup>6)</sup>	PP PVDF	PP PVDF	PP PVDF -20/ +80°C ~3.0 kg -20/+140°C ~4.5 kg
	<b>-FD</b> <b>-FA1</b>		<b>Anschluss / Typ</b> Connection / Type Raccord / Type	Flansch Flansch Sonder auf Anfrage	Flange Flange Special on request	Brides Brides Spécial nous consulter DIN / EN ANSI
	<b>-P</b>		<b>Membrane</b> Diaphragm Membrane	PTFE PTFE PTFE	Ø 200 mm p <sub>1</sub> : -120 ... max. + 200 mbar g Ø 200 mm p <sub>1</sub> : -1000 ... max. + 500 mbar g <sup>2,3)</sup> Ø 200 mm p <sub>1</sub> : -1000 ... max. +1.500 mbar g <sup>2,3)</sup>	
			<b>Federbereich<sup>1)</sup></b> p <sub>1</sub> , primär	<b>Horizontal<sup>4)</sup></b> 5 – 20 mbar 8 – 50 mbar 10 – 100 mbar 15 – 200 mbar 20 – 500 mbar <sup>2,4)</sup>	<b>Vertical<sup>5)</sup></b> 5 – 20 mbar 8 – 50 mbar 10 – 100 mbar 15 – 200 mbar 20 – 500 mbar <sup>2,4)</sup>	<b>Typ, Type, Type</b> LPSK, LPSK/D/Ds LPSK, LPSK/D/Ds LPSK, LPSK/D/Ds LPSK, LPSK/D/Ds LPSK, LPSK/D/Ds
			<b>Spring range<sup>1)</sup></b> p <sub>1</sub> , primary			<b>Dom, Dome, Dôme</b> (max 1000 mbar) (max 1000 mbar) (max 1000 mbar) (max 1000 mbar) (max 1000 mbar)
			<b>Plage de réglage<sup>1)</sup></b> p <sub>1</sub> , primaire	-15 – -3 mbar -60 – -10 mbar -120 – -20 mbar	-15 – -3 mbar -60 – -10 mbar -120 – -20 mbar	LPSK/N/NDs (min -1000 mbar) LPSK/N/NDs (min -1000 mbar) LPSK/N/NDs (min -1000 mbar)
			<b>180</b>	<b>Sitz</b> Seat Siège	18 mm, Kv = 6.5	
			<b>Optionen, Options, Options</b>			
			<b>/Sp</b> <b>/VA</b> <b>/Ws</b>	Eingestellt/plombiert V4A-Federdom Wetterschutz	Adjusted and sealed SST spring dome Weather protection	Ajusté et plombé Avec dôme en INOX Avec protection contre les intempéries
			<b>/C2.2</b> <b>/Cp</b>	EN 10204-2.2 Einstellprotokoll	EN 10204-2.2 Test protocol	EN 10204-2.2 Protocole de réglage
<b>Beispiel, Example, Exemple</b>						
<b>LPSK</b>	<b>25</b>	<b>PV</b>	<b>-FD</b>	<b>-P</b>	<b>50</b>	<b>180</b>
						<b>/Sp/C2.2</b>

## Hinweise,

- 1) Vordruckabhängigkeit
- 2) Nur mit V4A-Federdom
- 3) Nur mit Feder 500
- 4) Für Flüssigkeiten und Gase
- 5) Für Gasanwendungen
- 6) Nur für benetzte Teile

## Hints,

- 1) Primary pressure effect
- 2) With SST spring dome
- 3) With spring 500 only
- 4) For liquids and gas
- 5) For gas applications
- 6) Wetted parts only

## Remarque

- 1) Dépendance de la pression primaire
- 2) Uniquement avec dôme INOX
- 3) Uniquement avec ressort de 500
- 4) Pour liquides et gaz
- 5) Pour les applications de gaz
- 6) Uniquement pour pièces en contact

# 15 Code: LPS25, relief valve

LPS LPS/D LPS/Ds LPS/N LPS/NDs	IP40 / IP54 (Option /Ws)	<b>Funktion</b>	Überdruck	Gauge Pressure	Pression relative	520 mbar
	IP68	Function	Domgesteuert	Dome loaded	Dôme	2000 mbar (2500 mbar)
	IP40	Fonction	Eigen/Pilot	Integral/Pilot	Pilotage/direct	2000 mbar (2500 mbar)
	IP40 / IP54 (Option /Ws)		Fremd/Pilot	Remote/Pilot	Pilotage/indirect	-220 mbar
	IP40		Negativdruck	Negative pressure	Pression negative	-1000mbar
	<b>25</b> DN25, PN40	<b>Größe</b>	Einbaulänge	Lay length	Encombrement	100x120mm, ~6.0 kg
	<b>25</b> 1", 150 lbs	<b>Size</b>	Einbaulänge	Lay length	Encombrement	100x120mm, ~6.0 kg
	<b>25</b> 1", 300 lbs	<b>Dimension</b>	Einbaulänge	Lay length	Encombrement	~7.3 kg
	<b>25</b> G¾ (¾" BSP)		Einbaulänge	Lay length	Encombrement	~4.7 kg
	<b>25</b> G1 (1" BSP)		Einbaulänge	Lay length	Encombrement	78x120 mm, ~4.5 kg
	<b>25</b> G1.5 (1½" BSP)		Einbaulänge	Lay length	Encombrement	~4.5 kg
	<b>25</b> ¾" NPT-F		Einbaulänge	Lay length	Encombrement	~4.7 kg
	<b>25</b> 1" NPT-F		Einbaulänge	Lay length	Encombrement	78x120 mm, ~5.1 kg
	<b>25</b> 1.5" NPT-F		Einbaulänge	Lay length	Encombrement	~5.4 kg
	<b>25</b> TriClamp		Einbaulänge	Lay length	Encombrement	62x120mm, ~4.9 kg
	<b>S</b>	<b>Material</b>	Edelstahl	SST	INOX	1.4404
	<b>H</b>	<b>Material</b>	Hastelloy C	Hastelloy C	Hastelloy C	C276
	<b>X</b>	<b>Matériaux</b>	Sonder auf Anfrage	Special on request	Spécial nous consulter	(PP, PVDF) <sup>1)</sup>
	<b>-FD</b>	DN25, PN40	<b>Anschluss/Typ</b>	Flansch	Flange	Brides
	<b>-FA1</b>	1", 150 lbs	Connection/Type	Flansch	Flange	Brides
	<b>-FA3</b>	1", 300 lbs	Raccord/Type	Flansch	Flange	Brides
	<b>-GD2</b>	G¾ (¾" BSP)		Gewinde	Thread	Fileté
	<b>-GD3</b>	G1 (1" BSP)		Gewinde	Thread	Fileté
	<b>-GD4</b>	G1.5 (1½" BSP)		Gewinde	Thread	Fileté
	<b>-GN2</b>	¾" NPT-F		Gewinde	Thread	Fileté
	<b>-GN3</b>	1" NPT-F		Gewinde	Thread	Fileté
	<b>-GN4</b>	1.5" NPT-F		Gewinde	Thread	Fileté
	<b>-TCB</b>	TriClamp		TriClamp	Ø 50.5 mm	DIN32676, B
	<b>-XX</b>		Sonder auf Anfrage	Special on request	Spécial nous consulter	DIN / EN
	<b>-P</b>	<b>Membrane</b>	PTFE	-20/+180 °C	Ø 200 mm	
	<b>-V</b>	<b>Diaphragm</b>	Viton®	-20/+130 °C	Ø 200 mm	
		<b>Federbereich</b>	<b>Horizontal</b> <sup>2)</sup>	<b>Vertical</b> <sup>3)</sup>	<b>Typ, Type, Type</b>	<b>Dom, Dome, Dôme</b>
		p <sub>1</sub> , primär	8 – 13 mbar	3 – 8 mbar	LPS, LPS/D/Ds	(max 2013 mbar)
			10 – 25 mbar	5 – 20 mbar	LPS, LPS/D/Ds	(max 2025 mbar)
			13 – 55 mbar	8 – 50 mbar	LPS, LPS/D/Ds	(max 2055 mbar)
		Spring range	15 – 100 mbar	10 – 100 mbar	LPS, LPS/D/Ds	(max 2100 mbar)
		p <sub>1</sub> , primary	20 – 200 mbar	15 – 200 mbar	LPS, LPS/D/Ds	(max 2200 mbar)
			25 – 500 mbar	20 – 500 mbar	LPS, LPS/D/Ds	(max 2500 mbar)
			N/A*	-5 – 0 mbar	LPS/N, LPS/NDs	(min -850 mbar)
		Plage de réglage	-10 – -2 mbar	-15 – -3 mbar	LPS/N, LPS/NDs	(min -850 mbar)
		p <sub>1</sub> , primaire	-55 – -5 mbar	-60 – -10 mbar	LPS/N, LPS/NDs	(min -850 mbar)
			-115 – -15 mbar	-120 – -20 mbar	LPS/N, LPS/NDs	(min -850 mbar)
			-215 – -45 mbar	-220 – -50 mbar	LPS/N, LPS/NDs	(min -850 mbar)
		<b>180</b>	<b>Sitz</b>			
			Seat			
			Siège	Kv = 6.5 / 18 mm		
			<b>Optionen, Options, Options</b>			
		<b>/C</b>	C (Impulsleitung)	C (pulse line)	C (ligne d'impulsion)	G¾ (¾" BSP)
		<b>/E</b>	E (Drainage)	E (Drain)	E (Vidage)	G¾ (¾" BSP)
		<b>/S1</b> <sup>4)</sup>	Manometerstutzen	Gauge nozzle	Raccord manomètre	G¾ (¾" BSP, p <sub>1</sub> )
		<b>/S2</b> <sup>4)</sup>	Manometerstutzen	Gauge nozzle	Raccord manomètre	G¾ (¾" BSP, p <sub>2</sub> )
		<b>/Sp</b>	Eingestellt/plombiert	Adjusted and sealed	Ajusté et plombé	
		<b>/Ws</b>	Wetterschutz	Weather protection	Avec protection	IP54 PP / Polypropylen
		<b>/C2.2</b>	EN 10204-2.2	EN 10204-2.2	EN 10204-2.2	
		<b>/C3.1</b>	EN 10204-3.1	EN 10204-3.1	EN 10204-3.1	
		<b>/Cp</b>	Einstellprotokoll	Test protocol	Protocole de réglage	II 2 G Ex h IIB T6 Gb II 3 G Ex h IIC T6 Gc II 2 D Ex h IIIC T6 Db II 3 D Ex h IIIC T6 Dc
		<b>/Ex</b> <sup>3)</sup>	ATEX Zulassung	ATEX approval	Certificat ATEX	
		<b>/FDA</b>	FDA-Bescheinigung	FDA approval	Certificat FDA	
		<b>/Ff</b>	Öl- Fettfrei	Certificate degreasing	Sans Huile ni Graisse	
		<b>/LT</b>	Lecktest	Leakage test	Essai de fuite	
		<b>/XPZ</b>	Poliert mit Zertifikat	Polished w/certified	Poli, avec Certificat	
<b>Beispiel, Example, Exemple</b>						
LPS	25	S	-FD	-P	100	180 /Sp/C3.1/Cp/Ex

Öffnungsdruck [mbar]
Opening pressure
Pression de ouvre
≤ 4
≤ 8
~ 3...9
~ 5...15
~ 8...32
~ 10...80
≤ 2
≤ 4
~ 3...9
~ 5...15
~ 8...32

**Hinweise,**  
**N/A\*** nicht anwendbar  
<sup>1)</sup> Siehe Typ: LPSK...  
<sup>2)</sup> Für Flüssigkeiten & Gase  
<sup>3)</sup> Nur für Gasanwendungen  
<sup>4)</sup> Manometer optional verfügbar

**Hints,**  
 not applicable  
 See Type: LPSK...  
 For liquids and gas  
 Gas applications only  
 Pressure gauge optionally available

**Remarque**  
 non applicable  
 S.V.P. remarque aussi Type: LPSK...  
 Pour liquides et gaz  
 Pour les applications de gaz  
 Manomètre disponible en option